Hollymatic 180A Mixer Grinder

POWERFUL... TOUGH... EFFICIENT

The Hollymatic stainless steel Model 180A has been a standard of the industry for over 50 years. Designed for use in high-volume supermarkets, butcher shops, and small to medium sized processors, the 180A efficiently produces homogenous mixtures of ground product.

Now equipped with separate mix and grind motors that allow for push button shifting form mix to mix/ grind!

STANDARD FEATURES

- Interchangeable 32/42 or 52 grinding head
- 200 lb. capacity swing open hopper and removable grinding head assembly for easy cleaning
- ▶ 10 HP grind motor / 1 HP mix motor
- Push button shifting from mix to mix/grind
- Safety interlocked counter balanced lid
- Figure '8' mixing paddle for uniform blending
- One tool assembly and disassembly
- All stainless steel construction throughout the food contact area
- Adjustable operating height
- Shorter feed screw for minimum product temperature rise



All Hollymatic Grinders and Mixer Grinders are available in Gemini two grinder systems. Gemini systems allow for the advantage of continuous first and second grind production, thus decreasing production time and reducing the all important handling of the product.

The Hollymatic 180A has proven to be a wise choice for investment in profitability! For more information, contact Hollymatic or your local authorized Hollymatic dealer today!







Stainless Grinding Head



Push Button Controls



First Grind Mixing Paddle

OPTIONAL FEATURES

- No. 32/42 or 52 Grind Head
- Pneumatic foot switch
- Gemini (2) grinder systems
- Bulker portioning attachment
- First Grind Mixing paddle
- Left or Right hand controls


SPECIFICATIONS


- 180A GMG: Up to 120 lbs. per minute with #52 grinder head and 2nd grind paddles
- 825 lbs. (180A GMG)

Model 120 Bulker

AVAILABLE VOLTAGES

| 10 HP | 208V-230V | @ 60HZ, 3PH | 27.9A-25.2A |
|----------|-----------|--|---|
| | 460V | @ 60HZ, 3PH | 12.6A |
| | 190V-208V | @50HZ, 3PH | 30.2A-28.2A |
| | 380V-415V | @50HZ, 3PH | 15.1A-14.2A |
| | 575V | @ 60HZ, 3PH | 10.1A |
| 1 HP | 208V | @ 60HZ, 3PH | 3.5A |
| | 230V | @ 60HZ, 3PH | 3.1A |
| | 460V | @ 60HZ, 3PH | 1.7A |
| 825 lbs. | | | |
| | 1 HP | 1 HP 200V 190V–208V 380V–415V 575V 208V 230V 460V | 1 2 0 |





Hollymatic Warranty: Six (6) months from date of purchase. Refer to warranty certificate for terms and conditions. © Copyright Hollymatic Corporation. All Rights Reserved.



Hollymatic Corporation 600 E. Plainfield Road Countryside, Illinois 60525 708/579-3700 v. 708/579-1057 f. hollyinfo@hollymatic.com www.hollymatic.com